

Features:

- Two-way passive speaker with one I2" woofer and one 2" driver.
- Cabinet is made from polypropylene and special high-tech material in large injection mold. It's durable, anti-shock and has good damping characters.
- Voice coil in the I2" woofer is made from Ø75mm copper cladding aluminium ribbon wire.
- Heavy duty protective grille.
- The high frequency driver is protected by special design circuit to avoid being damaged when overload.
- Rotatable 90°×40° (H×V) dispersion horn makes it suitable for any performance purposes.
- Molded-in pole mount, easily suspended.
- Vertical or horizontal layout, can be used as a monitor or in any flying systems.
- Arrayable vertically in 4 layers or horizontally in more than 8 columns.












Model:NI2

Technical Parameters


System:	: Built-in Crossover Two Wa			ker
Driver Quantity:	•	12"×1(Bass)	1× Ø44mm Dr	iver
Frequency Response(-3dB):			60Hz-20KHz	
Frequency Response(-10dB):			55Hz-20KHz	
Sensitivity(dB/1M/1W):			95dB	
Impedance:			8 Ohm	
Recommendatory Power(RMS/W):			300 W	
Max Sound Level(dB/1M):			115dB	
Rotatable horn($H \times V$):			90°×40°	
Harmonic Distortion:			€	3%
Connectors:			NL4×2, +1-1	
Dimensions(WxDxHmm/pcs):		4	415×3371×609mm	
Packing Dimensions(W × D × H mm/pcs		ocs)	460×430×670mm	
Net Weight(Kg/pcs):			18Kg	
Gross Weight(Kg/pcs):			2	3Ka

PROFESSIONAL AUDIO SYSTEM







Frequency response, SPL/2.83v




Impedance curve





Harmonic distortion 106dB/2.5m, nominal impedance



Waterfall spectrum analysis







Two Way Crossover

Cosmetic changes may be made